SM4600T0BEV



1

CT.

SANY E-POWER

FFICIENT, ENVIRONMENTAL FRIENDLY AND FULLY ELECTRIC

X. 1

.

....



TERMINAL TRACTOR SM4600T0BEV

Battery capacity 281,9 kWh Drive mode 4 x 2 Wheel base 3400 mm Capacity 75 t Range up to 120 km

EQUIPMENT SM4600TOBEV

FULL ELECTRIC TERMINAL TRACTOR

- + High efficiency, low consumption
- + Cost savings due to efficient system
- + Fast charging with dual gun charging
- Wide field experience in electric machine

Travel speed max. 40 km/h Empty weight 10000 kg Overall weight 85 000 kg Dimensions 6060 x 2 550 x 3 100 mm Turning radius min. < 8000 mm

BATTERY

Туре	Lithium iron phosphate (LFP)
Capacity	281,9 kWh
Warranty period	The attenuation in 5 years shall not exceed 30 %
Fully discharge cycles	3000 times
Cooling mode	liquid
Continuous working time	up to 120 km / up to 18 hours

CHARGER

Charging duration Charging power

ELECTRIC MOTORS

Power Torque 120 kW / 240 kW (single motor) 1200 Nm / 2800 Nm

70 minutes

2*150 kW

CHASSIS

011/10/010	
Drive mode	4 x 2
Cab type	Cab Forward
Wheel base	3 400 mm
Axle load F/R	9.5t/30t
Rear axle	Air suspended
Ground clearance	200 mm
Max. tract weight	75t
Gradeability	5 % full load
5th wheel – hydraulic adjustable	1 180 mm – 1 530 mm
Capacity 5th wheel	32t
Acceleration (0 to 30 km/h)	≤ 25 seconds
Tire size	12.00 R22.5-18PR

TOP HIGHLIGHTS

LARGE LOAD CAPACITY, LONG BATTERY ENDURANCE

SANY electric terminal tractor use SANY's engineering vehicle heavy-load chassis. It has a maximum traction weight of 75 t; on the port ground, the battery endurance range can reach up to 120 km or the endurance time is up to 18 hours.

SAFE, EFFICIENT, LOW-COST

The protection level of the three-electric system meets IP67 or above and adopts CATL's advanced leakage detection system and SANY's remote monitoring system.

ECONOMICAL, EFFICIENT, RELIABLE

The tractor is equipped with an integrated thermal management system to ensure that the battery is always at a suitable temperature and has the lowest energy consumption. It has an auxiliary braking system to improve braking energy feedback and can operate continuously for more than 5 years.



Not all products are available in all markets. As part of our continuous improvement process, we reserve the right to modify specifications and designs without giving prior notice. The figures may contain additional options.



SANY EUROPE GmbH Sany Allee 1 D-50181 Bedburg Tel. +49 2272 90531 100 Fax +49 2272 90531 109 info@sanyeurope.com www.sanyeurope.com